

Product Data Sheet

CH1112WE/CH1112AE

Product	ECONOMY QUALITY INTERIOR ACRYLIC FLAT LATEX PAINT		
Code No.	CH1112WE, CH1112AE		
Type	INTERIOR ACRYLIC LATEX, FLAT FINISH		
Description	The # CH1112WE, Economy Quality Interior Flat Latex Paint is a vinyl acrylic interior flat latex. This product is very fast drying and it provides a quick cosmetic fresh appearance of a new paint job. It is easy to apply with very little spattering or roller drips. The finish shows good uniformity and color consistency. Its flat finish minimizes flashing on uneven surfaces. A highly alkaline primer sealer like the # CH1310WG, Good Quality Acrylic Latex Primer/ Sealer is recommended over all plaster and concrete substrates.		
Uses	Living rooms, Dens, Bedrooms, and Dining rooms.		
Colors	CH1112WEWhite and pastel tint colors CH1112AE Deep and accent tint colors		
Gloss	Flat less than 10 units at 60 and 85 degrees		
Coverage	400 - 500 sq. ft. (37 to 46 sq. m.) per 3.78 l. (Values obtained on primed, smooth and non-porous surfaces. Coverage figures do not include any loss due to surface imperfections, porosity, mixing and application)		
Dry time	To touch..... 1 - 2 hours Hard..... 2 - 3 hours Recoat..... 4 - 5 hours		
Thinning	Clean water		
Clean-up	Warm soapy water		
Application	Surface to be painted must be clean, dry and free from dust, dirt, wax, oil or stains that may transfer. All fillers must be fully dry and sanded smooth. Use the # CH1310WG Good Quality Acrylic Latex Primer Sealer as the base coat. Glossy surfaces should be dulled by sanding. Temperature should be above 7 deg. C. and the room must be ventilated to allow air flow. Do not apply in overly thick coats as this may cause cracking during the drying period.		
Methods	Brush	Polyester/Nylon	Use as supplied
	Roller	Low to Medium Pile (10 - 15 mm)	Use as supplied
	Spray	.015 - .018 tip	Use as supplied

All data on properties and application of the materials mentioned in this publication are given, to the best of our knowledge, based on our developmental work and practical experience. Before using our products, the user shall determine the suitability of the product for his independent use. In case of doubt, our technical staff will gladly assist you with expert advice. The data in this publication is subject to modification if deemed necessary to keep pace with new technical developments.