

# Product Data Sheet

CH1310WB

<b>Product</b>	<b>BEST QUALITY INT./EXT. ACRYLIC LATEX PRIMER / SEALER</b>		
<b>Code no</b>	<b>CH1310WB</b>		
<b>Type</b>	<b>INTERIOR / EXTERIOR ACRYLIC LATEX PRIMER SEALER</b>		
<b>Description</b>	The Best Quality Acrylic Latex Primer Sealer is a 100% Acrylic Latex Primer Sealer designed specially for the China market where exterior and interior walls are usually highly alkaline. The # CH1310WB is a deep penetrating primer sealer which could lock up the alkaline inside the concrete walls and forms a barrier to prevent the corrosive alkaline from damaging the top coats. Its superior sealing properties would enable topcoats to have sheen and colour uniformity over fillers and board surfaces. Due to its special acrylic polymer in the paint, it could also be used for interior walls.		
<b>Uses</b>	Exterior and interior concrete or plastered walls		
<b>Colors</b>	CH1310WB, translucent, it could be tinted to enhance hiding property for the topcoat		
<b>Gloss</b>	Flat		
<b>Coverage</b>	400 - 500 sq. ft. (37 to 46 sq. m.) per 3.78 l. (Values obtained on primed, smooth and non-porous surfaces. Coverage figures do not include any loss due to surface imperfections, porosity, mixing and application)		
<b>Dry time</b>	To touch ..... 30 - 90 minutes Hard ..... 2 - 3 hours.		
<b>Thinning</b>	Clean water		
<b>Clean-up</b>	Warm soapy water		
<b>Application</b>	Surface to be painted must be dry and clean of dirt, dust, oils and wax. Cracks and holes should be patched and sanded smooth. The # CH1310WB is recommended for new or repaired cement or plaster surfaces. Allow adequate dry time before sanding or application of finish coats. Normally, a 28 to 30 days cure period for concrete surfaces is recommended before painting. The # CH1310WB was found to perform better than other primers in the market when tested side by side on cement surfaces that were cured in less than the 28 days period. Nevertheless, a better paint job would always be resulted when the concrete is fully cured.		
<b>Method</b>	Brush	Polyester/nylon	Use as supplied
	Roller	Medium pile	Use as supplied
	Spray	.013 - .018 tip	Use as supplied

All data on properties and application of the materials mentioned in this publication are given, to the best of our knowledge, based on our developmental work and practical experience. Before using our products, the user shall determine the suitability of the product for his independent use. In case of doubt, our technical staff will gladly assist you with expert advice. The data in this publication is subject to modification if deemed necessary to keep pace with new technical developments.