

# Product Data Sheet

CH1332WB/CH1332AB

<b>Product</b>	<b>BEST QUALITY INTERIOR/EXTERIOR ACRYLIC EGGSHELL LATEX PAINT</b>		
<b>Code No.</b>	<b>CH1332WB, CH1332AB</b>		
<b>Type</b>	<b>INTERIOR/EXTERIOR ACRYLIC LATEX, EGGSHELL FINISH</b>		
<b>Description</b>	The # CH1332WB, CH1332AB Best Quality Interior/Exterior Eggshell Latex Paint is acrylic eggshell latex formulated to meet the performance requirement of the China residential and commercial markets. It has great washing and scrub ability and ideal for high traffic areas like hallway walls, children's bedrooms, kitchens and recreation rooms. Its acrylic formula provides great adhesion on newly primed or aged surfaces and resulted a highly alkaline resistant, good hiding and smooth finish. It is easy to apply, non-spattering and good touch-up properties. It is best for use on surfaces previously primed with the # CH1310WB Best Quality Acrylic Latex Primer/ Sealer which could resist the corrosive alkaline chemicals from cement and plaster walls.		
<b>Uses</b>	Hallways, Living rooms, Dens, Bedrooms, Dining rooms, Kitchens and Recreation Rooms, Exterior walls.		
<b>Colors</b>	CH1332WB .....White and pastel tint colors CH1332AB .....Pastel and darker tint colors		
<b>Gloss</b>	Eggshell ..... 10 - 15 units at 60 degrees		
<b>Coverage</b>	400 - 500 sq. ft. (37 to 46 sq. m.) per 3.78 l. (Values obtained on primed, smooth and non-porous surfaces. Coverage figures do not include any loss due to surface imperfections, porosity, mixing and application)		
<b>Dry time</b>	To touch..... 1 - 2 hours Hard..... 2 - 3 hours Recoat..... 4 - 5 hours		
<b>Thinning</b>	Clean water		
<b>Clean-up</b>	Warm soapy water		
<b>Application</b>	Surface to be painted must be clean, dry and free from dust, dirt, wax, oil or stains that may transfer. All fillers must be fully dry and sanded smooth. Use the # CH1310WB Best Quality Acrylic Latex Primer Sealer as the base coat. Glossy surfaces should be dulled by sanding. Temperature should be above 7 deg. C. and the room must be ventilated to allow air flow. Do not apply in overly thick coats as this may cause cracking during the drying period.		
<b>Methods</b>	Brush	Polyester/Nylon	Use as supplied
	Roller	Low to Medium Pile (10 - 15 mm)	Use as supplied
	Spray	.015 - .018 tip	Use as supplied

All data on properties and application of the materials mentioned in this publication are given, to the best of our knowledge, based on our developmental work and practical experience. Before using our products, the user shall determine the suitability of the product for his independent use. In case of doubt, our technical staff will gladly assist you with expert advice. The data in this publication is subject to modification if deemed necessary to keep pace with new technical developments.