

PLASTERPRIME
ACRYLIC STUCCO PRIMER
General Product Information

STIR THOROUGHLY! READ ALL INSTRUCTIONS CAREFULLY!

Modco PlasterPrime is a pure acrylic, medium bodied, primer paint that may be used as a primer and a substrate sealer. **Modco PlasterPrime** is designed as a substrate sealer for all the **Modco Decorative Products**. **Modco PlasterPrime** is available in natural white and our standard colors.

QUALITIES

Modco PlasterPrime is *non - toxic, weather resistant, fire retardant, will not crack or peel* and may be applied on either *interior or exterior* surfaces. **PlasterPrime** helps prepare the surface for better adhesion and reduces surface absorption, so that you have more time available to work and finish the **Modco Decorative Coatings**. **PlasterPrime** may be diluted with small amounts of cold water. Acrylics dry quickly in warm temperatures and **should not** be applied or stored below 5°C (degrees Celsius).

RECOMMENDED USES

Modco PlasterPrime may be used on most surfaces such as: concrete block, concrete walls, plywood, interior drywall, scratch and grey stucco, etc., **except plastic**. **PlasterPrime** will not prevent bleeding of water soluble surface stains!

COLOR TINTING

The **Modco Color Tint System** in a bottle is a unique system, whereby a consistent amount of color tint is supplied, held in a suspension and ready to use. The system provides a *color fast, fade resistant* finish when used to tint **Modco Decorative Coatings**. Use an equal amount with each pail (usually 1 bottle per pail) and you will achieve the **Modco Standard Colors**. An error free factor has been built in to assure color consistency.

Simply shake the bottle well, pour the contents into the pail of **Modco Decorative Coating** to be tinted, fill the bottle approximately half full with clear water and shake well to rinse. Pour the remaining liquid into the pail being tinted and then mix thoroughly.

The **Modco Color Tint System** is available in a number of **Modco Standard Colors**. The proper amount of color is predetermined for use with most of the **Modco Decorative Coatings**.



modco

TECHNOLOGY (CANADA) LTD.

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200

PLASTERPRIME
ACRYLIC STUCCO PRIMER
General Product Information

PLEASE NOTE

If diluting **Modco** products with water, use consistent volumes of cold water for each pail, always be consistent in your mixing in order to maintain consistent workability and color. If no color is added to the pail then the equivalent of 170ml (6oz.) of water per pail of product may be used to bring the product to the designed workability.

SURFACE PREPARATION

All surfaces must be clean, dry and free from dust, oil, grease, wax, rust or bleeding type stains. If the possibility of bleeding exists the surface should be painted with a stain blocking paint. For new or previously painted surfaces a coat of **Modco PlasterPrime** is recommended.

APPLICATION

Modco PlasterPrime is a versatile and easy to use product which is capable of adhering to smooth or porous surfaces. Apply an even coat as you would with a regular paint using a brush, sprayer or heavy – piled roller.

SPRAY APPLICATION

When spraying, a special orifice may be required because of the size of the abrasive particles. **Modco PlasterPrime** may be diluted with cold water.

CLEAN UP

Use hot water to clean up tools and spills.

COVERAGES

16 Liters will cover approximately
76 – 90 sq. meters (818 – 968 sq. ft.).

**COVERAGES WILL VARY DEPENDING ON POROSITY AND SURFACE
TEXTURE.**



modco

TECHNOLOGY (CANADA) LTD.

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200

PLASTERPRIME
ACRYLIC STUCCO PRIMER
General Product Information

SET TIME

1 – 3 hours.

DRY TIME

4 – 12 hours, depending on temperatures and humidity.

***CLOSE THE PAIL TO PREVENT DRYING OUT. WASH ALL TOOLS
IMMEDIATELY!***



modco
TECHNOLOGY (CANADA) LTD.

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200