

**PLASTERPRIME**  
**ACRYLIC STUCCO PRIMER**  
Technical Product Information

---

- DESCRIPTION:**..... Acrylic based, medium bodied, quartz paint. Can be used on most surfaces as a primer sealer for **Modco Decorative Coatings**. Non toxic. Weather resistant. Fire Retardant. May be tinted using **Modco Color Tint System**. For interior / exterior use.
- SUBSTRATE:**..... Apply on all solid, clean, building surfaces: block, concrete, plywood, drywall, **ModcoTex Base Sheets** or gypsum wallboard, etc. **DO NOT APPLY TO PLASTIC.**
- QUALITIES:**..... Versatile and easy to use. Provides a rough adhesion coat for **Modco Decorative Coatings**. Dries to an extremely hard finish. Resists most normal abuse. Finished product will “*breathe*”. Alkaline resistant. **WILL NOT PREVENT** bleeding of water soluble surface stains.
- PACKAGING:**..... 16 liter plastic pails.
- DANGER ZONE:**..... A – 0.
- GLOSS:**..... Matte.
- BINDER:**..... Acrylic copolymer.
- FILLERS:**..... Titanium dioxide, quartz and calcite.
- THINNERS:**..... Water.
- DILUTIONS:**..... Must be kept constant to maintain consistent color and workability.
- CLEANERS:**..... Hot water.
- STORAGE:**..... Excellent for 12 months or more in original unopened plastic pails. Keep away from frost or extreme heat.
- MIN. WORKING TEMP.:**..... 5°C (degrees Celsius) for substrate and ambient air temperature.
- COLOR:**.....  
White or any of the **Modco Standard Colors**. May also be tinted with the **Modco Color Tint System** or universal dispersion pigments to max. 5%.
- SPECIFIC GRAVITY:**..... +/- 1.8.
- COVERAGE** ..... 33 Kg per square meter depending on surface.
- SET TIME:**..... 1 – 3 hours.
- DRYING TIME:**..... 4 – 12 hours. Depends on temperature and humidity.



**modco**

**TECHNOLOGY (CANADA) LTD.**

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200

# **PLASTERPRIME**

## **ACRYLIC STUCCO PRIMER**

Technical Product Information

---

**APPLICATION:**..... All surfaces must be dry and free from dust, oil, grease, wax, rust and bleeding type stains. Apply as you would for regular paint with a brush or a roller. For spray applications use a hopper gun, texture sprayer or sprayer with special orifice because of abrasive particles.

Previously wallpapered walls and chipboard should be sealed with an oil based primer to prevent discoloration.

Always use the same color **PlasterPrime** as the decorative finish coat.

**COMBUSTIBILITY:** ..... Product is water based and has **NO FLASH** by close cup test.

Can4 – S102: Will withstand standard method of test for surface burning characteristics of building materials with the following rates or better as tested by the underwriters' laboratories of Canada.

**Modco PlasterPrime** applied at 5.0 M<sup>2</sup> / L in one coat over **Modco Trade Paint Primer** applied at 9.0M<sup>2</sup> / L in one coat as a base.

Classification or Rating  
(When Applied to Asbestos – Cement Board)

Flame Spread FSC (GWL)	Smoke Developed	Fuel Contributed
5 (5)	0	0

• For information on the following tests; product, weather heat, color, adhesion, mold, deformation, flexibility & additional tests please refer to the data sheets on **Modco** product testing.

All data on properties and application of the materials mentioned in this publication are given, to the best of our knowledge, based on our developmental work and practical experience. Before using our products, the user shall determine the suitability of the product for his independent use. In case of doubt, our technical staff will gladly assist you with expert advice. The data in this publication is subject to modification if deemed necessary to keep pace with new technical developments.



# modco

**TECHNOLOGY (CANADA) LTD.**

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200