

**STIR THOROUGHLY! READ ALL INSTRUCTIONS CAREFULLY!**

**Modco RynoTex** is a pure acrylic elastomeric based, light bodied, wall texture paint that can be used for a variety of purposes and gives an orange peel texture. It is a tough, durable, easily maintained product that will stand up to commercial or high traffic areas. Being moisture resistant, it stands up very well in kitchens, bathrooms, locker and dressing rooms, restrooms, etc. **Modco RynoTex** is available in natural white and our standard colors.

**QUALITIES**

**Modco RynoTex** is *non – toxic, weather resistant, fire retardant, will not crack or peel* and may be applied on either *interior or exterior* surfaces. Acrylics dry to an extremely hard finish enabling them to resist most normal abuse, but they still “*breathe*”. Some unique qualities of this product are: flexibility and elasticity; this allows the product to “*give*” when covering small hairline cracks. **RynoTex** may be diluted with small amounts of cold water. Acrylics dry quickly in warm temperatures and **should not** be applied or stored below 5°C (degrees Celsius).

**RECOMMENDED USES**

**Modco RynoTex** may be used on most surfaces such as: concrete blocks, concrete walls, plywood, interior drywall, smooth stucco, etc., **except plastic**.

**COLOR TINTING**

The **Modco Color Tint System** in a bottle is a unique system whereby a consistent amount of color tint is supplied, held in a suspension and ready to use. The system provides a color fast, fade resistant finish when used to tint **Modco Decorative Coatings**. Use an equal amount with each pail (usually 1 bottle per pail) and you will achieve the **Modco Standard Colors**. An error free factor has been built in to assure color consistency.

Simply shake the bottle well, pour the contents into the pail of **Modco Decorative Coating** to be tinted, fill the bottle approximately half full with clear water and shake well to rinse.



Pour the remaining liquid into the pail being tinted and then mix thoroughly. The **Modco Color Tint System** is available in a number of **Modco Standard Colors**. The proper amount of color is predetermined for use with most of the **Modco Decorative Coatings**.

### **PLEASE NOTE**

If diluting **Modco** products with water, use consistent volumes of cold water for each pail. Always be consistent in your mixing in order to maintain consistent workability and color. If no color is added to the pail then the equivalent of 170ml (6oz.) of water per pail of product may be used to bring the product to the designed workability.

### **SURFACE PREPARATION**

All surfaces must be clean, dry and free from dust oil, grease, wax, rust or bleeding type stains. Any surface holes or defects should be patched and smooth. For new or previously painted surfaces a coat of **Modco PlasterPrime** is recommended.

### **APPLICATION**

Used by itself, **Modco RynoTex** is a versatile and easy to use product which is capable of filling and sealing porous surfaces or of creating textures of a “*unique*” orange peel design. Apply an even coat as you would with a regular paint, use a foam texture roller or use a 12.7 mm – 31.2 mm (1/2" – 1 1/4") heavy – piled roller. Be sure to overlap and back roll creating an orange peel texture as the product sets. It is recommended to apply two coats allowing approximately 6 hours drying time between coats.

### **OPTIONS**

#### **MODCO RYNOTEX SYSTEM**

The **Modco RynoTex System** is **RynoTex** applied with two coats of **Modco AcraSeal** as a sealer coat. This optional method of application gives a protective gloss finish over the **RynoTex** application. Apply the two coats of **RynoTex** as per application instructions. Use a 9.5 mm (3/8") paint roller to apply a medium to heavy coat. A sprayer may also be used. Allow 24 hours drying time between coats and beware of lap marks. The surface will totally dry and cure usually within 7 days.



# **modco**

**TECHNOLOGY (CANADA) LTD.**

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200

***RYNOTEX***  
**SELF – PRIMING WALL TEXTURE**  
General Product Information

---

**SPRAY APPLICATION**

For walls and ceilings apply a sealer coat of latex or oil – based paint or **Modco PlasterPrime**. Use a hopper gun or texture sprayer to apply **Modco RynoTex** undiluted. The coverage will vary as to the size of aperture opening used.

**COVERAGES**

**16 Liters will cover approximately**  
36 – 50 sq. meters (388 – 538 sq. ft.).

**COVERAGES WILL VARY DEPENDING ON POROSITY OR SURFACE TEXTURE.**

**CLEAN UP**

Use hot water to clean up tools and spills.

**SET TIME**

2 hour.

**DRY TIME**

12 – 24 hours, depending on temperature and humidity.

**CLOSE THE PAIL TO PREVENT DRYING OUT. WASH ALL TOOLS**  
**IMMEDIATELY!**

**SPONGE TEXTURED ROLLER**



**modco**  
**TECHNOLOGY (CANADA) LTD.**

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200