
STIR THOROUGHLY! READ ALL INSTRUCTIONS CAREFULLY!

Modco SandFloat is a 100% acrylic elastomeric based decorative stucco containing 1 mm to 2.5 mm aggregate which is used to create the product appearance. **SandFloat** should be applied with a rust free trowel and floated with a plastic or stainless steel float to acquire the desired sand appearance. The aggregate in the product helps maintain a constant thickness during application. **Modco SandFloat** is available in natural white and a wide variety of custom colors.

QUALITIES

Modco SandFloat is *non – toxic, weather resistant, fire retardant, will not crack or peel* and may be applied on either *interior or exterior* surfaces. Acrylics dry to an extremely hard finish enabling them to resist most normal abuse, but they still “*breathe*”. Some unique qualities of this product are: flexibility and elasticity; this allows the product to “*give*” when covering small hairline cracks. **SandFloat** may be diluted with small amounts of cold water. Acrylics dry quickly in warm temperatures and **should not** be applied or stored below 5°C (degrees Celsius).

RECOMMENDED USES

Modco SandFloat may be used over most surfaces such as: concrete walls, smooth stucco coats, plywood, drywall, smooth masonry surfaces, expanded polystyrene foamboard as part of the **Modco Insulation System** and as a finish coat when used with the **ModcoTex System**, etc., **except plastic**.

COLOR TINTING

The **Modco Color Tint System** in a bottle is a unique system whereby a consistent amount of color tint is supplied, held in a suspension and ready to use. The system provides a color fast, fade resistant finish when used to tint **Modco Decorative Coatings**. Use an equal amount with each pail (usually 1 bottle per pail) and you will achieve the **Modco Standard Colors**. An error free factor has been built in to assure color consistency.

Simply shake the bottle well, pour the contents into any pail of **Modco Decorative Coating** to be tinted, fill the bottle approximately half full with clear water and shake well to rinse. Pour the remaining liquid into the pail being tinted and then mix thoroughly.



SANDFLOAT

Acrylic Elastomeric Stucco

General Product Information

The **Modco Color Tint System** is available in a number of **Modco Standard Colors**. The proper amount of color is predetermined for use with most of the **Modco Decorative Coatings**.

PLEASE NOTE

If diluting **Modco** products with water, use consistent volumes of cold water for each pail. Always be consistent in your mixing in order to maintain consistent workability and color. If no color is added to the pail then the equivalent of 170ml (6oz.) of water per pail of product may be used to bring the product to the designed workability.

SURFACE PREPARATION

All surfaces must be clean, dry and free from dust, oil, grease, wax, rust or bleeding type stains. Any surface holes or defects should be patched and smooth. For previously painted or new surfaces, a coat of **Modco PlasterPrime** is recommended in the same color as the finish coat that is to be applied.

APPLICATION

Used by itself, **Modco SandFloat** is a versatile and easy to use product which is capable of producing sand textured walls. Trowel on **Modco SandFloat** to the thickness of the aggregate with a rust free steel trowel. Let it set for 5 to 10 minutes, depending on temperature and humidity, then float the surface with a plastic or stainless steel float to achieve the sand appearance. For a smoother finish use a wet steel trowel to go over the surface. Clean your tools regularly to prevent sticking.

SPRAY APPLICATION

For walls and soffits, apply a sealer coat of **Modco PlasterPrime**. Use a hopper gun or texture sprayer to apply **Modco SandFloat**. The aperture opening and the dilution will dictate the design. Use an aperture that is larger than the size of the aggregate in the product. Dilution may be done with water depending on the effect required. Use a wet steel trowel to create a California knock down style finish.

NEW PLASTER AND STUCCO – INTERIOR OR EXTERIOR

Provide a smooth scratch and brown coat of stucco over tar paper and stucco wire or metal lath. Apply a sealer coating of **Modco PlasterPrime**. Apply **Modco SandFloat** as per the above application desired.



modco

TECHNOLOGY (CANADA) LTD.

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200

SANDFLOAT

Acrylic Elastomeric Stucco

General Product Information

CLEAN UP

Use warm water to clean up tools and spills.

COVERAGES

16 Liters will cover approximately

11 – 13 sq. meters (118 – 140 sq. ft.) in **Medium**.

13 – 15 sq. meters (140 – 162 sq. ft.) in **Fine**.

SET TIME

2 - 4 hours.

DRY TIME

24 hours, depending on temperature and humidity.

**CLOSE THE PAIL TO PREVENT DRYING OUT. WASH ALL TOOLS
IMMEDIATELY!**



SandFloat (Fine or
Medium)
Applied With Steel
Trowel and Finished
With Plastic Float



modco
TECHNOLOGY (CANADA) LTD.

Mail: 7610 - 116A Street, Delta, British Columbia, Canada, V4C 5Y2

Tel (604) 351-2742 Fax (604) 594-3200